

# fi-6140/fi-6240

## High Performance Color Duplex Scanners

The fastest and most advanced  
scanners in their class\*



- Fast, 60 ppm/120 ipm scanning in monochrome and grayscale
- Best in class 300 dpi color scanning at 40 ppm/80 ipm
- First scanners in their class to offer Intelligent MultiFeed Function (IMFF) as well as advanced Paper Protection technology
- Robust 50-page Automatic Document Feeder (ADF) with enhanced hard and embossed card scanning (Example: credit or healthcare cards)
- Comes with Kofax® VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro
- One-year Limited Warranty with available Advance Exchange program

\* The fi-6140/fi-6240 belongs to the class of A4 ADF color scanners whose scanning speeds meet or exceed 40 ppm / 80 ipm (color, A4, 200 dpi). This statement stood true as of October 2007.

**FUJITSU**

# fi-6140/fi-6240

## High Performance Color Duplex Scanners

The Fujitsu fi-6140 and fi-6240 scanners bring high performance and advanced features in a compact design

In addition to the fi-6140 scanner being the smallest scanner in its class, both models are able to scan an impressive 60 pages or 120 images per-minute in Monochrome or Grayscale (Letter @ 200dpi) as well as 40 pages or 80 images per-minute in Color (Letter @ 300dpi). Furthermore, the Fujitsu fi-6140 and fi-6240 models are the first scanners in their class to adopt high-end "fi series" functions such as:

- Paper Protection technology: Protects valuable documents by halting the scanning process when it recognizes that a jam is about to occur.
- Intelligent MultiFeed Function (iMFF): Simplifies pre-scanning preparation and improves efficiency by ignoring documents that trigger false multi-feed alerts such as an attached receipt or sticky note.
- Intelligent Capture Correction Function (iCCF): Auto-color recognition, auto-size detection, and auto de-skew correction provides dramatic efficiency by combining fast scanning with simultaneous high speed image processing.

Along with ultrasonic double-feed detection, long document scanning (up to 10 feet), dual interfaces (ultra SCSI and USB 2.0), and embossed card scanning, these scanners can continuously feed up to 3 hard cards (up to 1.4 mm thick) through the Auto Document Feeder (ADF).

### Fully Loaded One Box Solution

The Fujitsu fi-6140 and fi-6240 scanners conveniently include everything in the box to get organizations up and scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for the Fujitsu Advance Exchange Program, provides peace-of-mind. For full details on the Limited Warranty and on all Fujitsu service programs, go to [www.ImageService.com](http://www.ImageService.com) or call (800) 626-4686.

### About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc., a subsidiary of Fujitsu Ltd., is an established leader in the Document Imaging industry, delivering innovative scanning solutions and services that enable our customers to solve critical business productivity issues and streamline operations. We provide cutting-edge document capture and workflow solutions for business and personal environments, backed by a comprehensive portfolio of service and support programs.



ADOBE ACROBAT 9 STANDARD



### Fujitsu Computer Products of America, Inc.

<http://us.fujitsu.com/fcpa>  
1250 East Arques Avenue Sunnyvale, CA 94085-4701  
(800) 626-4686 (408) 746-7000 [info@fcpa.fujitsu.com](mailto:info@fcpa.fujitsu.com)

| Technical Specifications             |   |  |
|--------------------------------------|---|--|
| Model                                | fi-6140/fi-6240   |  |
| Image Sensor Type                    | fi-6140   | Color Charge Coupled Device (CCD) x 2                                    |
|                                      | fi-6240   | Color Charge Coupled Device (CCD) x 3                                    |
| Light Source                         | White cold cathode discharge lamp   |  |
| Optical Resolution                   | 600 dpi   |  |
| Output Resolution <sup>1</sup>       | Color (24 bit)  | 50 to 600 dpi<br>(adjustable by 1 dpi increments, 1200 dpi) <sup>2</sup> |
|                                      | Grayscale (8 bit)   |  |
|                                      | Monochrome  |  |
| Output Format                        | Color: 24 bit, 8 bit/4 bit; Grayscale: 8 bit, 4 bit; Monochrome: 1 bit  |  |
| AD Converter                         | 1024 levels (10 bit)  |  |
| Scanning Speeds                      |   |  |
| Output (Letter/A4 size) <sup>3</sup> | Simplex   |  |
|                                      | Duplex  |  |
| Color <sup>4</sup>                   | 200 dpi   | 40 ppm   |
|                                      | 300 dpi   | 40 ppm   |
| Grayscale <sup>4</sup> / Monochrome  | 200 dpi   | 60 ppm   |
|                                      | 300 dpi   | 40 ppm   |
| ADF Capacity <sup>5</sup>            | 50 Sheets (letter/A4, 20 lb.)   |  |
| Document size                        | ADF minimum   | 2 in. x 3 in. (52mm x 74mm)  |
|                                      | ADF maximum   | 8.5 in. x 14 in. (Legal)   |
|                                      | Flatbed (fi-6240 only)  | 8.5 in. x 11.69 in. (216mm x 297mm)                                      |
| ADF Feeding                          | Normal  | 11 to 56.2 lb. (41 to 210g/m <sup>2</sup> )                              |
| Paper Weight (Thickness)             | A8 sheets   | 34 to 56.2 lb. (127 to 210g/m <sup>2</sup> )                             |
|                                      | Card <sup>6</sup> (1.4mm) <sup>7</sup>  | Portrait and Landscape feeding <sup>8</sup>                              |
| Interface <sup>9</sup>               | Ultra SCSI (50m) / Hi gh Speed USB 2.0  |  |
| Physical Specifications              |   |  |
| Power requirements (auto-switching)  | 100 – 240 VAC, 50/60 Hz   |  |
| Power consumption                    | fi-6140   | 42W or less (Sleep: less than 6.2W)                                      |
|                                      | fi-6240   | 28 – 34 W, Energy saving mode: 12 W                                      |
| Dimensions (WxDxH) <sup>10</sup>     | fi-6140   | 11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm)                                |
|                                      | fi-6240   | 11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm)                               |
| Weight                               | fi-6140   | 9.24 lb. (4.2 kg)  |
|                                      | fi-6240   | 19.36 lb. (8.8 kg)   |
| Environmental compatibility          | ENERGY STAR <sup>®</sup> and RoHS   |  |
| Operating Environment                | Temperature   | 42° to 95° F (5° to 35° C)   |
|                                      | Relative humidity   | 20% to 80% (non-condensing)  |
| Inbox Contents                       | TWIN, ISIS <sup>™</sup> , USB cable, AC adapter   |  |
| Bundled Software                     | Adobe <sup>®</sup> Acrobat <sup>®</sup> Standard, Kofax <sup>®</sup> VRS <sup>®</sup> 4.x Professional and ScandAll Pro   |  |
| Options                              | Software IPC, Imprinter, (Flatbed Cover Black Background for fi-6240)   |  |
| OS Support                           | Microsoft <sup>®</sup> Windows <sup>®</sup> 2000 Professional / Microsoft <sup>®</sup> XP (32 bit/64 bit) / Microsoft <sup>®</sup> Windows Server <sup>™</sup> 2003 (32 bit/64 bit) / Microsoft <sup>®</sup> Windows Vista <sup>™</sup> (32 bit/64 bit)   |  |
| Feed Detection Features              | Ultrasonic Double Feed Detection Sensor<br>Paper Protection Sensor<br>Intelligent Multifeed Function  |  |
| Other Features                       | Ultrasonic Double Feed Detection, Intelligent Multi-Feed Function (iMFF), Paper Protection Function, Embossed Card Scanning Capability, Long Document Scanning, Automatic Color Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction, Selectable White & Black Background (in ADF only). |  |
| Limited Warranty                     | One-year. Advance Exchange program also available; restrictions apply. For full details, visit <a href="http://www.ImageService.com">www.ImageService.com</a> or call (800) 626-4686.   |  |
| Service Options                      | Post-Warranty: Advance Exchange Plus; restrictions apply.   |  |
|                                      | Consumables: ScanAid <sup>™</sup> kit. For full details, visit <a href="http://www.ImageService.com">www.ImageService.com</a> or call (800) 626-4686.   |  |
| Part Number                          | fi-6140   | PA03540-B005   |
|                                      | fi-6240   | PA03540-B505   |

1. Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.
2. Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher).
3. Actual scanning speeds are affected by data transmission and software processing times.
4. JPEG compressed figures.
5. Maximum capacity varies, depending upon paper weight.
6. Supports ISO7810 embossed cards
7. Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm).
8. Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feeding.)
9. Ultra SCSI interface cannot be used simultaneously with USB2.0.
10. Excluding the ADF paper chute and stacker



©2010 Fujitsu Computer Products of America, Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. Adobe and Acrobat are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft, SharePoint, Windows and Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ISIS is a registered trademark of Pixel Transitions, a division of Captiva Software Corporation. VRS is a registered trademark of Kofax Image Products, Inc. ABBYY FineReader are trademarks of ABBYY Software House. As an ENERGY STAR<sup>®</sup> Partner, Fujitsu Ltd. has determined that this product meets the ENERGY STAR<sup>®</sup> guidelines for energy efficiency. ENERGY STAR<sup>®</sup> is a U.S. registered trademark. All other trademarks are the property of their respective owners. All statements herein are valid only in the U.S. for U.S. residents, are based on normal operating conditions, are provided for informational purposes only, and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Computer Products of America, Inc. reserves the right to modify at any time without prior notice these statements, our products, their performance specifications, availability, price and warranty, post-warranty and service programs. Printed in the U.S.A. Qty. 5M DS38200310

